



- Compact size
- Electronic measuring arm
- Dynamic balancing programs

SBM 60/60 A/V85 A

ENTRY LEVEL WHEEL BALANCER

SBM 60/V85 A ENTRY LEVEL WHEEL BALANCER

The SBM 60/60 A/V85 A are electronic wheel balancers designed for low to medium volume workshops. Thanks to the new extreme versatility and compact size design, the electronic wheel balancers are suitable for working in narrowest environments and with all types of car, motorcycle and lightweight transportation wheels. Supplied with a TFT monitor (SBM V85 A), EASYFIT internal electronic measuring arm and a complete software package including all static and dynamic balancing programs. Thanks to the new wheel cover shape and the new weight holders both units are the perfect equipment in the workshop environment.

HIGHLIGHTS:

- New Ergonomic wheel cover shape
- New weight holder
- Up to 820 mm diameter
- Max wheel weight 65 kg
- Small footprint
- Internal electronic measuring arm for rim distance & diameter (SBM 60 A/V85 A)
- Optional, external electronic measuring arm for rim width
- Many holders for weights and tools
- Monitor TFT 19" (SBM V85 A)



WEIGHT HOLDER:

- Ergonomic weight holder for weights and tools
- Easily accessible



KEYBOARD:

- Intuitive 5 keys-keyboard raised for a better sensibility and accessible from any position



TECHNICAL DATA

	SBM 60/60 A	SBM V85 A
Power Supply	230V 1ph 50/60 Hz	230V 1ph 50/60 Hz
Balancing Speed (50-60Hz)	208 rpm (50Hz) / 250 (60 Hz)	208 rpm (50Hz) / 250 (60 Hz)
Max. Wheel Weight	65 Kg	65 Kg
Max. Wheel Diameter	820 mm	820 mm
Max. Wheel Width	420 mm	420 mm
Rim Diameter	8" – 26,5" / 10" – 24" Automatic	6" – 40" / 10" – 24" Automatic
Rim Width	2" – 20" / 1 – 20" Automatic	1" – 24" / 1 – 20" Automatic
Accuracy	1g / 0.05oz	1g / 0.05oz
Max. dimensions (WxDxH)	1100 x 1270 x 1280	1100 x 1270 x 1370

SCOPE OF DELIVERY:

- SBM 60/60 A/V85 A
- 19" TFT-Monitor / Double Digital LED Display
- Wheel protection
- Mechanic centering flange
- Cones:
 - 3 cones for mechanical locking system
- Weight plier
- Compass
- Calibration weight



ACCESSORY



PN: 1695 653 449

Light transport vehicle cone
(88 – 132 mm)




PN: 1695 606 200

Cone spacer



PN: 1695 654 849

Set of light truck cones
88 – 174 mm



PN: 1695 901 667

Kit of Off-Road cones from the back
incl. pins (40 mm) distance ring,
polyamide spacer



PN: 1695 554 043

3-4-5-hole Flange



PN: 1695 655 294

Set of QuickPlates
(4-, 5-, 6-holes-plates)



PN: 1695 600598

Electronic rim width measurement arm
(SBM 60 A/V85 A)



PN: 1695 656 698

DuoExpert system (3 collets in a case,
54 – 78 mm)



PN: 1695 656 570

Kit demo box for passenger car



PN: 1695 654 039

Basic motorbike wheel centring kit
(14 mm)



PN: 1695 654 060

Monolever wheel centring kit+shaft
(19 mm)



PN: 1695 606 300

Fourth cone (Ø 120-174 mm)

Sicam S.r.l. Società Unipersonale
A Bosch Group Company
Via G. Corradini | 42015 Correggio RE Italy
Tel. +39 0522 643-311 | Fax +39 0522 637-760
E-mail: sales@sicam.it | www.sicam.it